

Search 



All 3M Products Innovation About 3M

United States  [Change](#)

Industrial Adhesives & Tapes

[Products](#) | [Applications](#) | [Industries](#) | [Capabilities](#) | [Support](#)

[Where to Buy](#)

[United States](#) > [All 3M Products](#) > [Manufacturing and Industry](#) > [Industrial Adhesives & Tapes](#) > [3M Tapes & 3M Adhesives](#) > [Fasteners](#) > [3M™ Dual Lock™ Reclosable Fasteners](#) > 3M™ Dual Lock™ Reclosable Fastener SJ3541 400 Black, 2 in x 50 yd 0.23 in (5.8 mm), 1 per case Bulk

3M™ Dual Lock™ Reclosable Fastener SJ3541 400 Black, 2 in x 50 yd 0.23 in (5.8 mm), 1 per case Bulk

3M ID 70070430007 UPC# 00021200864513 Part Number SJ3541 3M Product Number SJ3541



[View All Images](#)

3M™ Dual Lock™ Reclosable Fastener SJ3541 has a rubber based adhesive on the back of a black, polypropylene reclosable fastener. 3M™ Dual Lock™ Reclosable Fastener SJ3540 has a 400 stems per square inch with a 0.23 inch engaged thickness. The closure life is 1,000 times.

- A black fastener with mushroom shaped stems that is backed with a rubber based pressure sensitive adhesive.
- Type 400 stem density polyolefin fastener which mates to Type 170 or 250.
- Designed to bond to many plastics, powder coated paints and other low surface energy materials.
- General Industrial, Packaging, Point of Purchase Displays, Exhibits, Electronics, Construction, Furniture and Maintenance, Repair and Operations (MRO).
- Attach Doors, Access Panels, Signs and Display Components.

[Where to Buy](#)

• [Print](#)

Need Help?

• [Share](#)

Questions? We can help
[Contact Us](#)

Like [Sign Up](#) to see what your friends like.

Overview

Documents

3M™ Dual Lock™ Reclosable Fastener SJ3541 has low temperature performance, with a temperature resistance of up to 120 degrees fahrenheit and is for indoor use only. This product is for use with many plastics (acrylic, polycarbonate and AS, powder coated paints and low surface energy materials (polypropylene and polyethylene).

Specifications

Adhesive Type	Rubber
Brand	Dual Lock
Closure Life	1000
Color	Black
Engaged Thickness	0.23 Inch
Flame Retardant	No
Indoor/Outdoor	Indoor
Industries	Construction, Furniture, General Industrial, Retail, MRO, Electronics, Packaging
Length	50 Linear Yard
Length (Metric)	45.72 m
Liner Thickness	5 mil
Liner Type	White Polyolefin
Low Profile	No

Maximum Operating Temperature (Celsius)	49 Degree Celsius
Maximum Operating Temperature (Fahrenheit)	120 Degree Fahrenheit
Product Form	Roll
Stem Density	400
Width	2 Inch
Width (Metric)	50.8 mm

3M: [News](#) | [Careers](#) | [Partners & Suppliers](#) | [Investor Relations](#) | [MSDS Search](#) | [Transport Information Search](#) | [Contact 3M](#)

[Legal Information](#) | [Privacy Policy](#)

© 3M 2014. All Rights Reserved.

