

Part Number: 5302F1



Security & Sound, #18-4c, TC, Shielded, CMG-FPL-PLTC-ER, Water-Blocked

# **Product Description**

Security & Sound Cable, Rated-CMG-FPL-PLTC-ER, 4-18 AWG stranded tinned copper conductors with PVC insulation, waterblocking tape, Beldfoil® shield and PVC jacket

# **Technical Specifications**

# **Product Overview**

Suitable Applications:		ns:	Low Voltage, Water-Blocked for Use in Underground Ducts, PLTC-ER, FPL, Intercom, Sound, Audio
Physi	Physical Characteristics (Overall)		
Conductor			
AWG	Stranding	Material	No. of Conductors
18	7x26	TC - Tinned Copper	4
Condu	ctor Count:		4
Conductor Size:			18 AWG

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.010 in

#### Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

# Outer Shield Material

Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Aluminum/Polyester	100 %	TC - Tinned Copper	20	(7x28)

#### **Outer Jacket Material**

Material	Nominal Diameter	Separator Material
PVC - Polyvinyl Chloride	0.259 in	Waterblocking Tape

## **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR
6.6 Ohm/1000ft	6.6 Ohm/1000ft	15.25 Ohm/1000ft

Foil(s) or Copper Tape(s)

## Capacitance

# Nom. Capacitance Conductor to Conductor 40 pF/ft

Voltage

Shielding:

voitage

UL Voltage Rating

## **Temperature Range**

UL Temp Rating:	105°C
Operating Temp Range:	-30°C To +105°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	42 lbs/1000ft
Max Recommended Pulling Tension:	102 lbs
Min Bend Radius/Minor Axis:	2.75 in

## **Standards**

NEC Articles:	800, 760, 725
NEC/(UL) Specification:	CMG, FPL, PLTC, PLTC-ER
CEC/C(UL) Specification:	CMG

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-11-06
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4/IEEE 1202 Vertical Tray Flame Test
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No	

## **Part Number**

#### Variants

Item #	Color	Footnote
5302F1 0101000	Black	С
5302F1 0021000	Red	С
ootnote:		

## © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.