1		2		3		4	5	
		S100 4 4 4 4 4 4 4 4 4 4 4 4 4	0- 	RECOMMENDED		CONTACT MATERIAL: CONTACT TYPE: STAN CONTACT TYPE: STAN CONTACT PLATING: S SHIELDING: BRASS NI QUALITY CLASS: 1500 ENVIRONMENTAL OPERATING TEMPER/ COMPLIANCE: LEAD F ELECTRICAL CURRENT RATING: 1. WORKING VOLTAGE: 1 INSULATOR RESISTAN	G: UL94-V0 COPPER ALLOY /PED ELECTIVE GOLD PLATED MATING CYCLES ATURE: -40°C UP TO +105°C REE AND ROHS 5 A MAX 30 VAC NCE: >1000 MΩ NDING VOLTAGE: 750 VAC/MIN SE: 20 mΩ MAX	
RoHS Compliant			PROJECTION:	GENERAL TOLERAN		-0-0-		
			APPROVAL: NPr	.X = +/_ 0.2 .XX = +/_ 0.2 UNIT: MM	15 WÜRTH E	LEKTRONIK N: USB 2.0 TYPE A UP RIGHT	SIZ	IZE
Q 21-AUG-15	PIN NUMBER ADDED	AK	7	SCALE:				4

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĪK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	ld
В]	SCALE:			٢
A	10-SEP-14	PDF	QL]	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			