APPI	LICAE	BLE STAN	DARD									
		OPERATING		55.00 TO 05.0	20 (1)		RAGE			10.00 TO 00.0	<b>O</b> (2)	
		TEMPERATURE RANGE VOLTAGE CURRENT		-55 °C TO 85 °	,C (1)		MPERATURE RANGE ERATING HUMIDITY			-10 °C TO 60 °C		
RAT	TING			100 V AC		RANG	ΞE			40 % TO 80 %		
				0.5 A		STORAGE RANGE		1UMIDITY 40 % TO 70 % (			(2)	
			SPECIFICATIONS									
	ITE	-M		TEST METHOD				RI	=OUII	REMENTS	ОТ	AT
CON		CTION		TEOT WILTHOU	<u> </u>			171		KLIVILIVIO	العا	1771
		AMINATION	VISUALI	LY AND BY MEASURING IN	STRUME	NT.	ACCOF	RDING	ΓΟ DR	AWING.	×	×
MARK	ING		CONFIRMED VISUALLY.								×	×
ELEC	CTRIC	CHARAC	TERISTI	CS								
CONTACT RESISTANCE			100 mA (DC OR 1000 Hz).				40 mΩ MAX.				×	T -
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD			20 mV MAX, 1 mA(DC OR 1000Hz)				50 mΩ MAX .				×	_
INSULATION			250 V DC				100 MΩ MIN.				×	† <b>-</b>
RESISTANCE			222 / 42 505 /								×	
VOLTAGE PROOF  MECHANICAL CHAR			300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.					<u> </u>
					NECTOR		IN OFF	TION FO	2005	70.451.846.7	×	
INSERTION AND WITHDRAWAL FORCES			MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE: 70.4 N MAX. WITHDRAWAL FORCE: 8.0 N MIN.					-
MECHANICAL OPERATION			100 TIMES INSERTIONS AND EXTRACTIONS.			S.	<ol> <li>CONTACT RESISTANCE: 50 mΩ MAX.</li> <li>NO DAMAGE, CRACK AND LOOSENESS</li> </ol>				×	_
VIBRATION			FREQUENCY 10 TO 55 Hz, AMPLITUDE: 1.5 mm,				OF PARTS.  ① NO ELECTRICAL DISCONTINUITY OF  1 μs.					_
SHOCK			AT 2 h FOR 3 DIRECTIONS.  490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms				② NO DAMAGE, CRACK AND LOOSENESS ×					
			AT 3	TIMES FOR 3 DIRECT		is	UF I	PARIS.				
		MENTAL C		TERISTICS								
DAMP HEAT (STEADY STATE)			EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				-			TANCE: 50 mΩ MAX.	×	-
RAPID CHANGE OF TEMPERATURE			TEMPERATURE-55 $\rightarrow$ +15 $\sim$ +35 $\rightarrow$ +85 $\rightarrow$ +15 $\sim$ +35 $\circ$ C TIME 30 $\rightarrow$ MAX 5 $\rightarrow$ 30 $\rightarrow$ MAX 5 min				<ul> <li>INSULATION RESISTANCE:100 MΩ MIN.</li> <li>NO DAMAGE, CRACK AND LOOSENESS OF PARTS.</li> </ul>				×	_
CORROSION SALT MIST			UNDER 5 CYCLES.  EXPOSED IN 5 % SALT WATER SPRAY FOR				① CONTACT RESISTANCE: 50 mΩ MAX.				×	_
HYDROGEN SULPHIDE			48 h.  EXPOSED IN 3 PPM FOR 96 h.				② NO HEAVY CORROSION.					_
			(TEST STANDARD: JEIDA 38)									
RESISTANCE TO			1) REFLOW SOLDERING : 250 °C MAX,				NO DEFORMATION OF CASE OF					-
SOLDERING HEAT			: 220 °C MIN, FOR 60 s				EXCESSIVE LOOSENESS OF THE TERMINALS.					
			2) SOLDERING IRONS : 360 °C, FOR 5 s									-
SOLDERABILITY			SOLDERED AT SOLDER TEMPERATURE, 240±3°C, FOR IMMERSION DURATION, 3 s.				A NEW UNIFORM COATING OF SOLDER X — SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.					_
	COUN	г р	 ESCRIPTION	ON OF REVISIONS		DESIG	NED	ED		CHECKED		TE
⚠							APPROVED CHECKED					
REM		THIS STORAG	E INDICATE	EINCLUDED WHEN ENERGIZED.  CATES A LONG-TERM STORAGE STATE					-	HS. OKAWA		6. 30 6. 28
				id product before the board mounted.			DESIGNE		NED	TS. MIYAKI	08. 06. 2	
							DRAWN			TS. MIYAKI	08. 06. 26	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test						DF	RAWIN	AWING NO. ELC4-084983				
1.	25	SI	PECIFICATION SHEET			PART	NO. F		FX	X6-80S-0. 8SV (71)		
U,	J	HIROSE ELECTRIC CO., LTE				CODE	NO.	CL576-0107-4-71			$\wedge$	1/1