MALLORY Mallor	y Sonale	rt Products	Part #: JT028-RG-CD			
Sales Outline Drawing				Revision:	В	
Specifications:						
Stack Number:	1	2				
LED Color:	RED	GREEN				
Connection Wires:	Red and Brown	Green and Brown				
LED Current Draw:	<50mA	<40mA				
Rated Voltage:		24 VAC/DC				
Operating Voltage:	20-28 VAC/DC					
Total Max Current:		<90mA				
Operating Temperature:	<u> </u>	-25° ~ +60°C				
Lens Color:	<u> </u>	Opaque White				
Material:	ABS FR15U					
Mounting Method:		Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut				
Weight Typical (g):	210					
NEMA 12:		Approved				
Options:		Please contact factory.				
Dimensions: Inches	•	cUL Recognized			ROHS Compliant	
ı	3.8 [9	³ 5,4] 				
r	/— RE:	D				
		\	wi	re		
		GREEN				
	4 5 544 4 03					
	4.5	[114.3]				
	Ø0.88 [Ø22.2] KNOCK OUT - FOR WIRES					
	`					
		2.4 [61.8]	,			
			/			
			()	
	2.7 [68.3]—		· · · · · · · · · · · · · · · · · · ·		
	TOP VIEV	\^/		MOUNTING		
	DIAGRAM					
LED OPERATION: CONN	IECT STACK COL	OR WIRE TO POWER A	ND DDOWN WID	E TO DOWED		
LED OPERATION. JCONN	ECT STACK COL	OR WIRE TO POWER A	IND PROMIN MIK	E TO POWER.		